

Таблица 41

Габаритные, установочные и присоединительные размеры

Типоразмер двигателя	Число полюсов	Габаритные размеры, мм						Установочные и присоединительные размеры, мм																									
		L	LC	AD	HD	P	AC	E	EA	B	BB	T	LA	C	R	F	FA	A	AB														
BA80M	2, 4, 6	355	410	145	300	200	190	50	50	100	125	3,5	14	50	0	6	6	125	155														
BA112M	2, 4, 6, 8	495	560		360	300	255	80	60	140	175	4		70		10	8	190	230														
BA132S	4, 6, 8	460	548		395	350	290				80	80		175			89	10	10	216	260												
BA132M	2, 4, 6, 8	498	586											178					215	10	216	260											
BA160S	2 4, 6, 8	710	832	260	490	350	340	110	178	230	5	17	108	0	12	12	254	304															
BA160M	2 4, 6, 8														740				862	14	12												
	BA180S	2 4	690																			805	121	16	14	14	279	320					
BA180M		2 4, 6, 8													730				845	14	16								14	279	320		
	BA200M	2 4, 6, 8	765	880	305	560	450						410			140	110	267				345	16	133	18	16	318	395					
BA200L		2 4, 6, 8													805				920	140	110								305	383	18	16	18
	BA225M	2 4, 6, 8	840	955																													
BA250S, M		2 4, 6, 8													990				1135	465	710								550	550	140	140	311, 349
	BA280S, M	2 4, 6, 8	1140	1285	140	170	368, 419	510	6	23	190	20	18	457		560																	
BA280S, M		2 4, 6, 8													1170		1315	140	170			368, 419	510	6	23	190	22	18					

Таблица 41 (продолжение)

Габаритные, установочные и присоединительные размеры

Типоразмер двигателя	Число полюсов	Установочные и присоединительные размеры, мм															
		AA	H	GD	GF	GA	GC	HA	HC	D	DA	K	M	S	N	45°	22,5°
BA80M	2,4,6	38	80	6	6	24,5	24,5	10	196	22	22	10	165	M10	130	45°	--
BA112M	2,4,6,8		112	8	7	35	31	14	257	32	28	12	265	15	230		
BA132S	4,6,8	42	132		8	8	41		41	292	38		38	15	300		
BA132M	2,4,6,8		8	8	41	41	292	38	38								
BA160S	2	50	160	8	8	45	45	20	362	42	42	15	300	19	250	45°	--
BA160M	4,6,8			9		51,5				48							
	2			8		45				42							
	4,6,8			9		51,5				48							
BA180S	2	60	180	10	9	52	52	22	398	48	48	19	350	19	300	45°	--
BA180M	4			9		59				55							
	2			9		52				48							
	4,6,8			10		59				55							
BA200M	2	90	200	11	10	64	59	28	435	60	55	19	400	19	350	45°	22,5°
BA200L	4,6,8			10		59				55							
	2			10		59				60							
	4,6,8			11		64				60							
BA225M	2	100	225	10	11	59	64	30	480	55	60	24	500	19	450	45°	22,5°
	4,6,8			11		69				65							
BA250S, M	2	100	250	11	12	69	74,5	30	-	65	70	24	500	19	450	45°	22,5°
	4,6,8			12		79,5				75							
BA280S, M	2	120	280	12	11	74,5	69	30	-	70	65	24	600	24	550	45°	22,5°
	4,6,8			14		85				80							